



**floored.online**

# PALACE OAK VERSAILLES

VERSAILLES COLLECTION  
900 X 18 X 900MM

## ENGINEERED PRODUCT SPECIFICATION DATASHEET

PRODUCT DESIGN	INFORMATION
Board Size	900 x 18 x 900mm
Product code	D1417003
Species	European oak (Quercus Petraea)
Floor Type	Multi-layer European oak
Construction	Engineered
Top Layer	4mm
Surface finish	Unfinished
Treatment	Light Brushed Sanded No other surface treatment
Profile	As per drawing
Box quantity	2 panels per pack
Pack size	1.62m <sup>2</sup>

GRADING	INFORMATION
CRITERIA Grade	Rustic A / Nature: This grading contains some knots, some sapwood and some colour variation. Maximum knot size is restricted to circa 25mm so it tends to have an overall balanced appearance due to fewer knots. Knots are filled to match the natural timber however may vary between boards and batches.
Filler	Allowed (All defects will be filled - small outbroken surface defects can occur)
Putty colour	Brown
Moisture content	8-10%
Gloss level	N/A
Plywood	Birch plywood core with ash balance backing
Bevel	1mm Bevel long sides (GO4)
Panel length	+/-0.7mm
Panel width	+/-0.7mm
Board thickness	+/-0.3mm
Bow (length) (max)	10mm per linear metre
Weight	+/-600kg m <sup>3</sup>

TECHNICAL	INFORMATION
CE marking / DOP	DOP WD_LF_005. Available on request with our office or can be downloaded on
Thermal conductivity	www.floored.online. $\lambda = 0.17 \text{ W/mk}$
Thermal insulation value	$R = 0.115 \text{ m}^2 \text{ k/w}$
Class of reaction to fire	Dfl - S1
Brinnell hardness	Average HB 3.7
European standard	EN 14342:2005 wood flooring , EN 12524:2000 building materials
Formaldehyde emission	E1
EUTR	Responsibly sourced under EUTR regulations
Underfloor Heating	Yes please follow installation guidelines

INSTALLATION & STORAGE	INFORMATION
Installation	Glue down installation only. Please refer to the floored.online installation instructions included in each carton. Also available on www.floored.online
Warranty	20 year structural warranty
Usage	Indoor use only
Storage	Store flat & on a stable surface. Place product in the room at least 72 hours before installation to allow for acclimatisation.
Air moisture	40 - 60%
Temperature	18-22 degrees celsius

## FLOOR CARE & MAINTENANCE

### Room Conditions:

Timber likes pleasant room conditions similar to humans: A room temperature of 20° and humidity of about 50%. The recommended range for timber flooring should be 18-22° and humidity 40-60%. A humidity controller may be required. All rooms which have timber flooring should ideally be maintained at the above. For underfloor heating the surface temperature of the wood surface should not exceed 25°celsius.

### Protecting your floor:

To preserve quality and beauty of your floor we recommend you use protective pads and caster cups under chairs and furniture legs. If there is a door leading outside from the room where you have installed your hardwood flooring, use a door mat to catch the dirt and absorb the humidity. Never use a rubber matt, with styrofoam or plastic backing. If you must move heavy pieces of furniture (e.g. refrigerator, piano, etc.), never slide them directly over the flooring. Instead, place a piece of carpet facedown between the legs and the flooring and pull the carpet to move the furniture. The floor should be monitored every 6-12 months to inspect the conditions of the surface.

*For further information please refer to the Floor Care and Maintenance manual included in the pack or alternatively visit [www.floored.online](http://www.floored.online)*

## INSTALLATION & WARRANTY

All floored.online floors must be installed by a professional approved installer who has the necessary skills and will take each site circumstance into consideration. Our warranty is only valid on floors which have been installed by an approved flooring installer to BS8201. All floors must be installed as per our installation instructions. (Available on [www.floored.online](http://www.floored.online))



*The grading image used in this datasheet is intended only as a guide of what the final product may look like. No rights can be taken from it. This technical data sheet was developed by our associated manufacturing partner. At the time of issuing this datasheet, all information is correctly stated. The company reserves the right to update or amend the specifications of this product at any time without prior notice to third parties.*